Subject: register mail account in kloxo db
Posted by hamed.ramzi on Wed, 22 Feb 2012 19:18:55 GMT
View Forum Message <> Reply to Message

dear friends:

I am faced with a difficult to create an email account under php.
for Registered mail in two databases.

1-kloxo db
2-example db

source code for register db2:

```
else if($_REQUEST['action'] == 'signup')
{
 $tpl->assign('pageTitle', $lang_user['signup']);

 // sign up ip lock?
 if($am_prefs['regenabled'] == 'yes'
  && ($am_prefs['user_count_limit'] == 0 || BMUser::GetUserCount() <
$am_prefs['user_count_limit']))
 {
  $res = $db->Query('SELECT COUNT(*) FROM {pre}users WHERE reg_ip=? AND
reg_date>?',
   $_SERVER['REMOTE_ADDR'],
   time()-$am_prefs['reg_iplock']);
  $row = $res->FetchArray();
  $res->Free();

  if($row[0] != 0)
  {
   // block sign up
   $tpl->assign('msg', $lang_user['reglock']);
   $tpl->assign('page', 'nli/regdone.tpl');
  }
  else
  {
   $showForm = true;

   if(isset($_POST['do']) && $_POST['do']=='createAccount')
   {
    $showForm = false;
    $invalidFields = array();
    $errorInfo = '';

    //
    // check fields
    //

    // email domain
    $suEMailDomain = trim($_POST['email_domain']);
    if(!in_array($suEMailDomain, explode(':', $am_prefs['domains'])))
```

```
 $invalidFields[] = 'email_domain';

// email
$suEMailLocal = trim($_POST['email_local']);
$suEMail = $suEMailLocal . '@' . $suEMailDomain;
if(!BMUser::AddressValid($suEMail) || !BMUser::AddressAvailable($suEMail)
 || BMUser::AddressLocked($suEMailLocal)
 || strlen($suEMailLocal) < $am_prefs['minuserlength'])
 $invalidFields[] = 'email_local';

// first name
$suFirstname = trim($_POST['firstname']);
if(strlen($suFirstname) < 2)
 $invalidFields[] = 'firstname';

// last name
$suSurname = trim($_POST['surname']);
if(strlen($suSurname) < 2)
 $invalidFields[] = 'surname';

// 'strasse'-group
if($am_prefs['f_strasse'] != 'n')
{
 // street
 $suStreet = trim($_POST['street']);
 if((strlen($suStreet) < 3) && (strlen($suStreet) > 0 || $am_prefs['f_strasse'] == 'p'))
  $invalidFields[] = 'street';

 // no
 $suNo = trim($_POST['no']);
 if((strlen($suNo) < 1) && (strlen($suNo) > 0 || $am_prefs['f_strasse'] == 'p'))
  $invalidFields[] = 'no';

 // zip
 $suZIP = trim($_POST['zip']);
 if((strlen($suZIP) < 3) && (strlen($suZIP) > 0 || $am_prefs['f_strasse'] == 'p'))
  $invalidFields[] = 'zip';

 // city
 $suCity = trim($_POST['city']);
 if((strlen($suCity) < 3) && (strlen($suCity) > 0 || $am_prefs['f_strasse'] == 'p'))
  $invalidFields[] = 'city';

 // country
 $suCountry = (int)$_POST['country'];
 if($am_prefs['f_strasse'] == 'p' && !in_array($suCountry, array_keys(CountryList())))
  $invalidFields[] = 'country';

 // zip/city check?
 if(!in_array('zip', $invalidFields)
  && !in_array('city', $invalidFields)
  && !in_array('country', $invalidFields)
```

```
  && $am_prefs['plz_check'] == 'yes'
  && !ZIPCheck($suZIP, $suCity, $suCountry))
 {
  $invalidFields[] = 'zip';
  $invalidFields[] = 'city';
  $errorInfo .= ' ' . $lang_user['plzerror'];
 }
}
else if($am_prefs['f_strasse'] == 'n')
{
 $suStreet = $suNo = $suZIP = $suCity = '';
 $suCountry = $am_prefs['std_land'];
}

// 'telefon'-field
if($am_prefs['f_telefon'] != 'n')
{
 $suPhone = trim($_POST['phone']);
 if((strlen($suPhone) < 5) && (strlen($suPhone) > 0 || $am_prefs['f_telefon'] == 'p'))
  $invalidFields[] = 'phone';
}
else if($am_prefs['f_telefon'] == 'n')
{
 $suPhone = '';
}

// safecode
if($am_prefs['f_safecode'] == 'p')
{
 $code = Safecode::GetCode((int)$_POST['codeID']);
 if(!isset($_POST['safecode'])
  || strlen($code) < 4
  || strtolower($_POST['safecode']) != strtolower($code))
  $invalidFields[] = 'safecode';
 if(strlen($code) >= 4)
  Safecode::ReleaseCode((int)$_POST['codeID']);
}

// 'fax'-field
if($am_prefs['f_fax'] != 'n')
{
 $suFax = trim($_POST['fax']);
 if((strlen($suFax) < 5) && (strlen($suFax) > 0 || $am_prefs['f_fax'] == 'p'))
  $invalidFields[] = 'fax';
}
else if($am_prefs['f_fax'] == 'n')
{
 $suFax = '';
}

// 'altmail'-field
if($am_prefs['f_alternativ'] != 'n')
```

```
    {
     $suAltMail = trim($_POST['altmail']);
     if((strlen($suAltMail) > 0 || $am_prefs['f_alternativ'] == 'p') &&
(!BMUser::AddressValid($suAltMail) || ($am_prefs['alt_check'] == 'yes' &&
!ValidateMailAddress($suAltMail))))
      $invalidFields[] = 'altmail';
    }
    else if($am_prefs['f_alternativ'] == 'n')
    {
     $suAltMail = '';
    }

    // 'mail2sms_nummer'-field
    if($am_prefs['f_mail2sms_nummer'] != 'n'
     || $am_prefs['reg_smsvalidation'] == 'yes')
    {
     $suMobileNr = trim(ereg_replace('[^0-9]', '', str_replace('+', '00',
$_POST['mail2sms_nummer'])));
     if((strlen($suMobileNr) < 6) && (strlen($suMobileNr) > 0 || $am_prefs['f_mail2sms_nummer']
== 'p'
      || $am_prefs['reg_smsvalidation'] == 'yes'))
      $invalidFields[] = 'mail2sms_nummer';
    }
    else if($am_prefs['f_mail2sms_nummer'] == 'n')
    {
     $suMobileNr = '';
    }

    // password
    $suPass1 = $_POST['pass1'];
    $suPass2 = $_POST['pass2'];
    if(strlen($suPass1) < 3 || $suPass1 != $suPass2 || $suPass1 == $suEMailLocal)
    {
     $invalidFields[] = 'pass1';
     $invalidFields[] = 'pass2';
     $errorInfo .= ' ' . $lang_user['pwerror'];
    }

    // coupon
    $suCoupon = isset($_POST['code']) ? trim($_POST['code']) : '';
    if($suCoupon != '' && !BMUser::CouponValid($suCoupon))
    {
     $invalidFields[] = 'code';
     $errorInfo .= ' ' . $lang_user['signupcouponerror'];
    }

    // tos
    if(!isset($_POST['tos']) || $_POST['tos'] != 'true')
     $errorInfo .= ' ' . $lang_user['toserror'];

    // profile fields
    $suProfile = array();
```

```
$res = $db->Query("SELECT id,rule,pflicht,typ FROM {pre}profilfelder");
while($row = $res->FetchArray())
{
 $feld_ok = false;
 $feld_name = 'field_' . $row['id'];
 switch($row['typ'])
 {
 case FIELD_CHECKBOX:
  $feld_ok = true;
  $suProfile[$row['id']] = isset($_POST[$feld_name]);
  break;
 case FIELD_DROPDOWN:
  $feld_ok = true;
  if($feld_ok)
   $suProfile[$row['id']] = $_POST[$feld_name];
  break;
 case FIELD_RADIO:
  $feld_ok = isset($_POST[$feld_name]);
  if($feld_ok)
   $suProfile[$row['id']] = $_POST[$feld_name];
  break;
 case FIELD_TEXT:
  $feld_ok = (trim($row['rule']) == '') || (ereg($row['rule'], $_POST[$feld_name]));
  if(isset($_POST[$feld_name]))
   $suProfile[$row['id']] = $_POST[$feld_name];
  break;
 }
 if(($row['pflicht']=='yes' || (isset($_POST[$feld_name]) && strlen($_POST[$feld_name]) >
0)) && (!$feld_ok))
  $invalidFields[] = $feld_name;
}
$res->Free();

// go on
if(count($invalidFields) > 0)
{
 // errors => mark fields red and show form again
 $showForm = true;
 $tpl->assign('errorStep', true);
 $tpl->assign('errorInfo', $lang_user['checkfields'] . $errorInfo);
 $tpl->assign('invalidFields', $invalidFields);
}
else
{
 // create account
 $userId = BMUser::CreateAccount($suEMail,
  $suFirstname,
  $suSurname,
  $suStreet,
  $suNo,
  $suZIP,
  $suCity,
```

```
    $suCountry,
    $suPhone,
    $suFax,
    $suAltMail,
    $suMobileNr,
    $suPass1,
    $suProfile);

   // successful?
   if($userId !== false && $userId > 0)
   {
    // redeem coupon?
    if($suCoupon != '')
    {
     $theNewUser = _new('BMUser', array($userId));
     $theNewUser->RedeemCoupon($suCoupon);
    }

    // account created
    Add2Stat('signup');
    $showForm = false;
    $tpl->assign('msg',    sprintf($am_prefs['usr_status'] == 'locked'
            ? $lang_user['regdonelocked']
            : $lang_user['regdone'], $suEMail));
    $tpl->assign('page',    'nli/regdone.tpl');


    // module handler
    ModuleFunction('AfterSuccessfulSignup', array($userId, $suEMail));
   }
   else
   {
    // error occured
    $showForm = true;
    $tpl->assign('errorStep',   true);
    $tpl->assign('errorInfo',   $lang_user['regerror']);
    $tpl->assign('invalidFields',  array());
   }
  }
 }

 if($showForm)
 {
  // codes?
  $res = $db->Query('SELECT COUNT(*) FROM {pre}codes');
  $row = $res->FetchArray(MYSQL_NUM);
  $res->Free();
  $tpl->assign('code', $row[0] > 0);

  // safe code
  if($am_prefs['f_safecode'] == 'p')
   $tpl->assign('codeID', Safecode::RequestCode());
```

```
    // profile fields?
    $profilfelder = array();
    $res = $db->Query('SELECT feld,pflicht,id,extra,typ FROM {pre}profilfelder');
    while($row = $res->FetchArray())
    {
     array_push($profilfelder, array(
      'feld'   => $row['feld'],
      'pflicht'  => $row['pflicht']=='yes',
      'id'   => $row['id'],
      'extra'   => explode(',', $row['extra']),
      'typ'   => $row['typ']
     ));
    }
    $res->Free();
    if(count($profilfelder) > 0)
     $tpl->assign('profilfelder', $profilfelder);

    // required fields
    $tpl->assign('f_strasse',    $am_prefs['f_strasse']);
    $tpl->assign('f_telefon',    $am_prefs['f_telefon']);
    $tpl->assign('f_fax',     $am_prefs['f_fax']);
    $tpl->assign('f_alternativ',   $am_prefs['f_alternativ']);
    $tpl->assign('f_mail2sms_nummer',  $am_prefs['reg_smsvalidation'] == 'yes' ? 'p' :
$am_prefs['f_mail2sms_nummer']);
    $tpl->assign('f_safecode',    function_exists('imagepng') ? $am_prefs['f_safecode'] : 'n');

    // show page
    $tpl->assign('countryList',  CountryList());
    $tpl->assign('defaultCountry', $am_prefs['std_land']);
    $tpl->assign('tos',    HTMLFormat($lang_custom['tos']));
    $tpl->assign('domainList',   explode(':', $am_prefs['domains']));
    $tpl->assign('page',    'nli/signup.tpl');
   }
  }
 }
 else
 {
  // sign up disabled
  $tpl->assign('msg', $lang_user['regdisabled']);
  $tpl->assign('page', 'nli/regdone.tpl');
 }
}
```

Comfortably in the user registration system, and is not problem.

how fix:
I want after register a mail account and With the same data as a Account in the table in the db1 "database kloxo mailaccount " also be record.

source signup tpl

```
<form action="index.php?action=signup" method="post" onsubmit="submitSignupForm()">
<input type="hidden" name="do" value="createAccount" />
<input type="hidden" name="transPostVars" value="true" />
<input type="hidden" name="codeID" value="{$codeID}" />

<div id="signupSpinner" style="display:none;width:100%;">
<center><img src="{$tpldir}images/load_32.gif" border="0" alt="" /><br /><br /></center>
</div>
<div id="signupForm" style="display:;">
<table class="nliTable">
 <!-- sign up -->
 <tr>
  <td class="nliIconTD"><img src="{$tpldir}images/main/signup.gif" border="0" alt="" /></td>
  <td class="nliTD">

   <h3>{lng p="signup"}</h3>

   {lng p="signuptxt"} {if $code}{lng p="signuptxt_code"}{/if}

   {if $errorStep}
   <br /><br /><div class="errorText">{$errorInfo}</div>
   {else}
   <br />
   {/if}

   <br />
  </td>
 </tr>

 <!-- address -->
 <tr>
  <td class="nliIconTD"><img src="{$tpldir}images/main/address.gif" border="0" alt="" /></td>
  <td class="nliTD">

   <h3>{lng p="wishaddress"}</h3>

   <table>
    <tr>
     <td class="formCaption"><label for="email_local">{lng p="wishaddress"}:</label></td>
     <td class="formField">
      <input type="text" name="email_local" id="email_local" value="{$_safePost.email_local}"
size="20" onblur="checkAddressAvailability()" />
      <select name="email_domain" id="email_domain" onblur="checkAddressAvailability()">
       {foreach from=$domainList item=domain}<option value="{$domain}"{if
$_safePost.email_domain==$domain} selected="selected"{/if}>@{$domain}</option>{/foreach}
      </select>
     </td>
     <td class="formStatus" id="addressAvailabilityIndicator"> </td>
    </tr>
   </table>

   <br />
```

```
  </td>
 </tr>

 <!-- address -->
 <tr>
  <td class="nliIconTD"><img src="{$tpldir}images/main/contact.gif" border="0" alt="" /></td>
  <td class="nliTD">

   <h3>{lng p="contactinfo"}</h3>

   <table>
    <tr>
     <td class="formCaption">* <label for="firstname">{lng p="firstname"}:</label></td>
     <td class="formField">
      <input type="text" value="{$_safePost.firstname}" name="firstname" id="firstname"
size="35" />
     </td>
     <td class="formStatus" id="firstnameValidity"> </td>
    </tr>
    <tr>
     <td class="formCaption">* <label for="surname">{lng p="surname"}:</label></td>
     <td class="formField">
      <input type="text" value="{$_safePost.surname}" name="surname" id="surname" size="35"
/>
     </td>
     <td class="formStatus" id="surnameValidity"> </td>
    </tr>

    {if $f_strasse!="n"}
    <tr>
     <td class="formCaption">{if $f_strasse=="p"}*{/if} <label for="street">{lng
p="streetnr"}:</label></td>
     <td class="formField">
      <input type="text" value="{$_safePost.street}" name="street" id="street" size="35" />
      <input type="text" value="{$_safePost.no}" name="no" id="no" size="8" />
     </td>
     <td class="formStatus" id="streetValidity"> </td>
    </tr>
    <tr>
     <td class="formCaption">{if $f_strasse=="p"}*{/if} <label for="zip">{lng
p="zipcity"}:</label></td>
     <td class="formField">
      <input type="text" value="{$_safePost.zip}" name="zip" id="zip" size="8" />
      <input type="text" value="{$_safePost.city}" name="city" id="city" size="35" />
     </td>
     <td class="formStatus" id="zipValidity"> </td>
    </tr>
    <tr>
     <td class="formCaption">{if $f_strasse=="p"}*{/if} <label for="country">{lng
p="country"}:</label></td>
     <td class="formField">
      <select name="country" id="country">
```

```
      {foreach from=$countryList item=country key=id}
      <option value="{$id}"{if (!$_safePost.country && $id==$defaultCountry) ||
($_safePost.country==$id)} selected="selected"{/if}>{$country}</option>
      {/foreach}
     </select>
    </td>
    <td class="formStatus" id="zipValidity"> </td>
   </tr>
   {/if}

   {if $f_telefon!="n"}
   <tr>
    <td class="formCaption">{if $f_telefon=="p"}*{/if} <label for="phone">{lng
p="phone"}:</label></td>
    <td class="formField">
     <input type="text" value="{$_safePost.phone}" name="phone" id="phone" size="35" />
    </td>
    <td class="formStatus" id="phoneValidity"> </td>
   </tr>
   {/if}

   {if $f_fax!="n"}
   <tr>
    <td class="formCaption">{if $f_fax=="p"}*{/if} <label for="fax">{lng p="fax"}:</label></td>
    <td class="formField">
     <input type="text" value="{$_safePost.fax}" name="fax" id="fax" size="35" />
    </td>
    <td class="formStatus" id="faxValidity"> </td>
   </tr>
   {/if}

   {if $f_mail2sms_nummer!="n"}
   <tr>
    <td class="formCaption">{if $f_mail2sms_nummer=="p"}*{/if} <label
for="mail2sms_nummer">{lng p="mobile"}:</label></td>
    <td class="formField">
     <input type="text" value="{$_safePost.mail2sms_nummer}" name="mail2sms_nummer"
id="mail2sms_nummer" size="35" />
    </td>
    <td class="formStatus" id="mail2sms_nummerValidity"> </td>
   </tr>
   {/if}

   {if $f_alternativ!="n"}
   <tr>
    <td class="formCaption">{if $f_alternativ=="p"}*{/if} <label for="altmail">{lng
p="altmail"}:</label></td>
    <td class="formField">
     <input type="text" value="{$_safePost.altmail}" name="altmail" id="altmail" size="35" />
    </td>
    <td class="formStatus" id="altmailValidity"> </td>
   </tr>
```

```
    {/if}
   </table>

   <br />
  </td>
 </tr>

 <!-- password -->
 <tr>
  <td class="nliIconTD"><img src="{$tpldir}images/main/password.gif" border="0" alt="" /></td>
  <td class="nliTD">

   <h3>{lng p="password"}</h3>

   <table>
    <tr>
     <td class="formCaption">* <label for="pass1">{lng p="password"}:</label></td>
     <td class="formField">
      <input autocomplete="off" type="password" name="pass1" id="pass1"
onkeyup="passwordSecurity(this.value, 'secureBar')" size="35" />
     </td>
     <td class="formStatus" id="pass1Validity"> </td>
    </tr>
    <tr>
     <td class="formCaption">* <label for="pass2">{lng p="repeat"}:</label></td>
     <td class="formField">
      <input autocomplete="off" type="password" name="pass2" id="pass2" size="35" />
     </td>
     <td class="formStatus" id="pass2Validity"> </td>
    </tr>
    <tr>
     <td class="formCaption">{lng p="security"}:</td>
     <td class="formField">
      <div class="passwordSecurity">
       <div class="secureBar" id="secureBar" style="background:
url({$tpldir}images/main/securebar.jpg); width:0%;"> </div>
      </div>
     </td>
     <td class="formStatus"> </td>
    </tr>
   </table>

   <br />
  </td>
 </tr>

 {if $code}
 <!-- code -->
 <tr>
  <td class="nliIconTD">
```

```
  <h3>{lng p="code"}</h3>

  <table>
   <tr>
    <td class="formCaption"><label for="code">{lng p="code"}:</label></td>
    <td class="formField">
     <input type="text" value="{$_safePost.code}" name="code" id="code" size="35" />
    </td>
    <td class="formStatus" id="codeValidity"> </td>
   </tr>
  </table>

  <br />
 </td>
</tr>
{/if}

{if $profilfelder}
<!-- misc  -->
<tr>
 <td class="nliIconTD"><img src="{$tpldir}images/main/misc.gif" border="0" alt="" /></td>
 <td class="nliTD">

  <h3>{lng p="misc"}</h3>

  <table>
   {foreach from=$profilfelder item=feld}
   {assign var=fieldID value=$feld.id}
   {assign var=fieldName value="field_$fieldID"}
   <tr>
    <td class="formCaption" nowrap="nowrap">{if $feld.pflicht}*{/if} <label
for="field_{$feld.id}">{$feld.feld}:</label></td>
    <td class="formField">
     {if $feld.typ==1}
      <input size="35" name="field_{$feld.id}" id="field_{$feld.id}"
value="{$_safePost[$fieldName]}" type="text" />
     {elseif $feld.typ==2}
      <input type="checkbox" name="field_{$feld.id}" id="field_{$feld.id}"{if
$_safePost[$fieldName]} checked="checked"{/if} />
     {elseif $feld.typ==4}
      <select name="field_{$feld.id}" id="field_{$feld.id}">
       {foreach from=$feld.extra item=item}
        <option value="{$item}"{if $_safePost[$fieldName]==$item}
selected="selected"{/if}>{$item}</option>
       {/foreach}
      </select>
     {elseif $feld.typ==8}
      {foreach from=$feld.extra item=item}
       <input type="radio" id="field_{$feld.id}_{$item}" name="field_{$feld.id}" value="{$item}"{if
$_safePost[$fieldName]==$item} checked="checked"{/if} />
       <label for="field_{$feld.id}_{$item}">{$item}</label>  
      {/foreach}
```

```
      {/if}
     </td>
     <td class="formStatus" id="field{$feld.id}Validity"> </td>
    </tr>
    {/foreach}
   </table>

   <br />
  </td>
 </tr>
 {/if}

 {if $f_safecode!='n'}
 <!-- safecode -->
 <tr>
  <td class="nliIconTD"><img src="{$tpldir}images/main/safecode.gif" border="0" alt="" /></td>
  <td class="nliTD">

   <h3>{lng p="safecode"}</h3>

   <table>
    <tr>
     <td class="formCaption"> </td>
     <td class="formField">
      <img src="index.php?action=codegen&id={$codeID}" border="0" alt=""
style="cursor:pointer;"
onclick="this.src='index.php?action=codegen&id={$codeID}&rand='+parseInt(Math.random()*1
0000);" />
     </td>
     <td class="formStatus" id="safecodeValidity">
      <small>{lng p="notreadable"}</small>
     </td>
    </tr>
    <tr>
     <td class="formCaption" nowrap="nowrap">* <label for="safecode">{lng
p="safecode"}:</label></td>
     <td class="formField">
      <input type="text" maxlength="6" style="text-align:center;" name="safecode" id="safecode"
size="35" />
     </td>
     <td class="formStatus" id="safecodeValidity"> </td>
    </tr>
   </table>

   <br />
  </td>
 </tr>
 {/if}

 <!-- terms of service -->
 <tr>
  <td class="nliIconTD"><img src="{$tpldir}images/main/tos.gif" border="0" alt="" /></td>
```

```
  <td class="nliTD">

   <h3>{lng p="tos"}</h3>

   <textarea style="width: 98%; height: 120px;" readonly="readonly">{$tos}</textarea>

   <center>
    <br />
    <input type="radio"{if $_safePost.tos=='true'} checked="checked"{/if} name="tos"
value="true" id="tos_acc" /> <label for="tos_acc">{lng p="tosaccept"}</label>
    <input type="radio"{if $_safePost.tos!='true'} checked="checked"{/if} name="tos"
value="false" id="tos_nacc" /> <label for="tos_nacc">{lng p="tosnaccept"}</label>
   </center>

   <br />
  </td>
 </tr>

 <!-- submit -->
 <tr>
  <td class="nliIconTD"><img src="{$tpldir}images/main/signup.gif" border="0" alt="" /></td>
  <td class="nliTD">

   <h3>{lng p="submit"}</h3>

   <img src="{$tpldir}images/main/ip.gif" style="vertical-align: middle;" border="0" alt="" /> {lng
p="iprecord"}

   <br /><br />
   <center>
    <input type="submit" value="   {lng p="submit"}   " />
   </center><br />
  </td>
 </tr>
</table>
</div>
</form>
```

thanck you